

*2,000 g x 1 g, mini type*

# DIGITAL SCALE

Model : GM-2000R

*ISO-9001, CE, IEC1010*



**LUTRON ELECTRONIC**

*The Art of Measurement*

**DIGITAL SCALE ( 2000 g X 1 g ), Model : GM-2000R****DIGITAL SCALE ( 225 g X 0.1 g ), Model : GM-225G**

<b>FEATURES</b>	
* Microcomputer circuit with high accuracy & better performance.	
* High resolution & wide measuring capacity,	
* Heavy duty ABS housing plastic case.	
* 13 mm ( 0.5" ) digit size red LED display, easy read out.	
* Built-in unit adjustment, select by the internal slide switch.	

<b>SPECIFICATIONS</b>		
Features	Highly accurate, compact size, easy to carry & transportation. The design is available for office, Laboratory, home & other general application. Red LED, 4 digits,	
Display	13 mm ( 0.56" ) digit size.	
Measuring capacity	GM-2000R	2000 g/70 oz.
	GM-225G	225 g/8 oz.
Resolution	GM-2000R	1 g/0.05 oz.
	GM-225G	0.1 g/0.005 oz.
Min. display weight	GM-2000R	3 g/0.15 oz.
	GM-225G	0.3 g/0.015 oz.
Unit select	g or oz ( internal select )	
Accuracy (23 5 蛭)	GM-2000R : $\pm ( 0.2 \% + 1 d )$	
	GM-225G : $\pm ( 0.05 \% + 2 d )$ * <i>After calibration.</i>	
Sampling time	Approx. 0.8 second.	
Overload capacity	GM-2000R	Max. 3 kg.
	GM-225G	Max. 500 g.
Tare Control	Full capacity.	
Transducer	Load cell.	
Circuit	Exclusive microcomputer LSI circuit.	
Operating temperature	0 to 50 °C ( 32 to 122 °F ).	
Operating Humidity	Less than 80% RH.	
Size	Cabinet	15 x 14.5 x 4.8 cm ( 5.9 x 5.7 x 1.9 inch )
	Platform	15 x 10.5 cm ( 5.9 x 4.2 inch )
Weight ( w/o battery )	0.45 Kg ( 1 LB )	
Power supply	6 x 1.5V AA (UM-3) battery or DC 9V adapter ( optional ).	
Power consumption	Approx. DC 80 mA.	
Accessory included	Operation Manual.....1 PC.	
Optional adapter	AC to DC adapter ( 500 mA ).	