

HUMIDITY/TEMP. METER

DEW POINT, RS232, Data logger

Model : MY-91HT

ISO-9001, CE, IEC1010



LUTRON ELECTRONIC



The Art of Measurement

HUMIDITY METER

Model : MY-91HT

FEATURES

* Humidity + Temperature + Dew point are combined into one meter, intelligent and professional.
* 0.01 %RH resolution for the humidity reading, 0.01 degree resolution for the Temp. reading.
* Fast humidity measuring response time.
* High accuracy and high precision.
* Dew point measurement.
* Manual and auto manual data logger.
* Data logger function with flexible sampling time selection, can save max. 1000 reading data with recall.
* Just few panel buttons, easy operation.
* Microprocessor circuit assures maximum possible accuracy, provides special functions and features.
* Large LCD with two display, easy readout.
* Heavy duty & compact housing case, designed for easy carry out & operation.
* Records Maximum and Minimum readings with Recall.
* Auto shut off saves battery life.
* Data hold function for freezing the desired value on display.
* RS 232 PC serial interface.
* Show the humidity & temperature values on the LCD display at same time.
* Built-in low battery indicator.
* Wide humidity & temp. measuring range.
* Separate humidity & temp. probe, easy operation and remote measurement.

GENERAL SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.	
Display	LCD size : 52 mm x 38 mm dual function LCD display.	
Measurement Unit	Humidity : %RH (Relative Humidity) Temperature : °C or °F. Dew point : °C or °F.	
Response Time	5 to 30 seconds typically. <i>* Reach the 85% reading value</i>	
Temperature Compensation	Automatic temp. compensation for the humidity function.	
Sampling Time of Data Logger	Manual	Push the data logger button once will save data one time.
	Auto	1, 2, 10, 30, 60, 600, 1800, 3600 seconds.
Data Hold	Freeze the display reading.	
Memory Recall	Maximum & Minimum value.	
Sampling Time	Approx. 0.8 second.	
Power off	Auto shut off saves battery life or manual off by push button.	

Data Output	RS 232 PC serial interface.
Operating Temperature	0 to 50 °C.
Operating Humidity	Main instrument : Less than 85% R.H. Probe : 0 to 95 %RH.
Power Supply	DC 1.5 V battery (UM4, AAA) x 6 PCs, or equivalent.
Power Current	Approx. DC 4.6 mA.
Weight	336 g/0.74 LB. <i>* Battery is included.</i>
Dimension	Main instrument : 174 x 68 x 42 mm (6.9 x 2.7 x 1.7 inch). Humidity Sensor Probe : 197 mm (7.8 inch) in length.
Accessories Included	Instruction manual..... 1 PC Humidity probe..... 1 PC
Optional Accessories	* Hard Carrying case, CA-06 * Soft Carrying case, CA-05A * RS232 cable, UPCB-02 * USB cable, USB-01 * Data Acquisition software, SW-801-WIN * Data Logger software, SW-DL2005

ELECTRICAL SPECIFICATIONS (23± 5 °C)

Humidity/ Temperature

Humidity	Range	0 % to 95 % R.H.
	Resolution	0.01 % R.H.
	Accuracy	≥ 70% RH ± (3% reading + 1% RH). < 70% RH - 3% RH. ± 3% RH.
Temperature	Range	0 °C to 50 °C, 32 °F to 122 °F.
	Resolution	0.01 degree
	Accuracy	°C - 0.8 °C. °F - 1.5 °F.

Dew Point

°C	Range	-25.3 °C to 48.9 °C
	Resolution	0.01 °C
°F	Range	-13.5 °F to 120.1 °F.
	Resolution	0.01 °F.

Remark :

- * Dew Point display value is calculated from the Humidity/Temp. measurement automatically.
- * The Dew Point accuracy is sum accuracy value of Humidity & Temperature measurement..