

# TEMP. ( type K ) TRANSMITTER

**Model : TR-TMK1A4**

*ISO-9001, CE, IEC1010*



Temp. probe  
Optional



**LUTRON ELECTRONIC**

*The Art of Measurement*

# Temperature ( type K )

## TRANSMITTER

Model : TR-TMK1A4-500C

Model : TR-TMK1A4-100C

<b>Measure</b>	TR-TMK1A4-500C	TR-TMK1A4-100C
<b>Range</b>	0 to 500 °C	0 to 100 °C
<b>Output</b>	4 - 20 mA	
	TR-TMK1A4-500C	TR-TMK1A4-100C
	0 °C = 4 mA 250 °C = 12 mA 500 °C = 20 mA	0 °C = 4 mA 50 °C = 12 mA 100 °C = 20 mA
<b>External Adjustment</b>	ZERO VR SPAN VR	
<b>Power Supply</b>	90 - 260 ACV 50 Hz/60 Hz	
<b>Operation Temperature</b>	0 - 50 °C 32 - 122 °F	
<b>Operation Humidity</b>	Less than 80 %RH	
<b>Accessory Included</b>	Type K temperature probe is optional.	
<b>Optional Accessories</b>	Type K temperature probe : TP-01 TP-02A TP-03 TP-04	
<b>Mounting</b>	Din rail or Wall	
<b>Case</b>	ABS plastic	
<b>Others</b>	Type K standard input socket	

\* Appearance and specifications listed in this brochure are subject to change without notice.