

ANEMOMETER PROBE

Model : YK-200PAL

ISO-9001, CE, IEC1010



FEATURES

- * Anemometer probe (YK-200PAL) connect with YK-2001TM will become a professional Anemometer
- * Plastic vane structure, professional.
- * Low-friction vane wheel assures high accuracy measurement result both in high or low velocities.
- * Plug and play function, whenever you plug Anemometer probe in YK-2001TM, no calibration procedures are required to be done.
- * Multi-functions for air flow measurement: m/s, km/h, ft/min, knots, mile/h, °C, °F
- * Thermistor sensor for Temp. measurement fast response time.
- * Two temperature units, i.e. °C or °F.
- * Wide applications: air conditioning, heating systems measure air velocities, wind speed and temperature...etc.



 Lutron

LUTRON ELECTRONIC

The Art of Measurement

ANEMOMETER PROBE

Model : YK-200PAL

FEATURES
* Anemometer probe (YK-200PAL) connect with YK-2001TM will become a professional Anemometer
* Low-friction vane wheel assures high accuracy measurement result both in high or low velocities.
* Plug and play function, whenever you plug Anemometer probe (YK-200PAL) in YK-2001TM, no calibration procedures are required to be done.
* Multi-functions for air flow measurement: m/s, km/h, ft/min, knots, mile/h, °C, °F
* Thermistor sensor for Temp. measurement fast response time.
* Microprocessor circuit.
* Dual LCD display, show both wind velocity & temp. values.
* Records Maximum and Minimum readings with RECALL facilities.
* Data hold function.
* Auto shut off prolongs battery life.
* RS 232 PC serial interface.
* Two temperature units, i.e. °C or °F.
* Wide applications: air conditioning, heating systems measure air velocities, wind speed and temperature...etc.

GENERAL SPECIFICATION S	
Circuit	Custom one-chip microprocessor LSI circuit.
Measurement	m/s: 0.4 - 25.0 m/s km/h: 1.4 - 90.0 km/h mile/h: 0.9 - 55.9 mile/h knots: 0.8 - 48.8 knots ft/min: 80 - 4930 ft/min Temperature: 0 - 50 °C / 32 - 122 °F.
Memory Recall	Records Maximum and Minimum readings with RECALL facility.
Power off	Manual power off by push button or Auto power off (Not activated during memory record function).
Data Output	RS 232 PC serial interface.
Over load indication	Indicated by "- - - -".
Sampling Time	Approx. 0.8 second.
Operating Temperature	0 to 50 °C
Operating Humidity	Max. 80% RH.
Size	Probe : Round, 70 mm Dia. x 140 mm length.
Accessories Included	Instruction manual..... 1 PC. Anemometer probe..... 1 PC.

ELECTRICAL SPECIFICATION (23± 5°C)			
Anemometer			
<i>Unit</i>	<i>Range</i>	<i>Resolution</i>	<i>Accuracy</i>
m/s	0.4 - 25.0 m/s	0.1 m/s	± (2 % + 2 d) F. S.
km/h	1.4 - 90.0 km/h	0.1 km/h	
mile/h	0.9 - 55.9 mile/h	0.1 mile/h	
knots	0.8 - 48.8 knots	0.1 knots	± (2 % + 20 ft/min) F. S.
ft/min	80 - 4930 ft/min	1 ft/min	
F. S. = full scale m/s - meters per second km/h - kilometers per hour ft/min - feet per minute knots - nautical miles per hour mile/h - miles per hour (international knot)			
Temperature			
<i>Measuring Range</i>	0 °C to 50 °C / 32 °F to 122 °F		
<i>Resolution</i>	0.1 °C / 0.1 °F		
<i>Accuracy</i>	± 0.8 °C / 1.5 °F		

* Appearance and specifications listed in this brochure are subject to change without notice.